



TRETFORD ROLL

Product Description:

- Uniquely constructed natural fibre contract carpet

Construction	Ribbed
Pile Content	80% Goat Hair, 15% Nylon, 5% Viscose
Secondary Backing	Jute
Width	2m
Pile Weight	1200 gr/m ²
Total Weight	2750 gr/m ²
Total Height	7mm
Average Roll Length	30.00lm

Impact Sound Insulation	BS 2750: 1990 This carpet meets the requirements of the building regulations by a useful margin.
Sound Absorption	BS EN 20354: 1993 (250-2000Hz) is 0.21
Thermal Retention	1.76 Togs
Thermal Conduction	5.68 w/m ²
Permanent Antistatic	IBM and ICL Electrical Resistance: Tested at 40% RH and 20°C and passed
Light fastness	BS 1006: 1990 5-6 very slight to none
Water Fastness	BS 1006: 1990 4 very slight
Rubbing Fastness	BS 1006: 1990 4 very slight
Flammability	BS 4790 (Hot Metal Nut Test) Low radius of ignition BS EN ISO 9239-1 Cfl-S1
BREEAM Rated	A+

Guarantees:

- 5 year heavy commercial wear
- 5 year anti shock
- Full details of conditions and limits of guarantees available upon request



2009/533

JOSEPH HAMILTON & SEATON
RELAY PARK, RELAY DRIVE, TAMWORTH STAFFORDSHIRE, B77 5PR

TELEPHONE: (01827) 831400 TELEFAX: (01827) 831401
EMAIL: sales@jhscarpets.com

Registered Office: Gorseley Lane Coleshill Birmingham B46 1JU England HFD Ltd Registered in England and Wales No. 2674152